



Stærð	A	B	B1	C	D	E	F	GA	H	HA	K	AA	AB	BA1	BA2	BB	HD	LA	P	M	N	T	L	S
200	318	305		133	55	110	16	59.0	200	32	19	80	400	113	113	380	520	16.5	400	350	300	5	850	19
225S4	356	286	311	149	60	140	18	64.0	225	34	19	85	440	115	115	380	570	18	450	400	350	5	930	19
225M2	356	286	311	149	55	110	16	59.0	225	34	19	85	440	115	115	380	570	18	450	400	350	5	900	19
225M4-6	356	286	311	149	60	140	18	64.0	225	34	19	85	440	115	115	380	570	18	450	400	350	5	930	19
250M2	406	349		168	60	140	18	64.0	250	37	24	90	480	135	135	445	635	23	550	500	450	5	1,010	19
250M4-6	406	349		168	65	140	18	69.0	250	37	24	90	480	135	135	445	635	23	550	500	450	5	1,040	19
280S2	457	368	419	190	65	140	18	69.0	280	40	24	105	550	130	165	520	720	23	550	500	450	5	1,135	19
280S4-6	457	368	419	190	75	140	20	79.5	280	40	24	105	550	130	165	520	720	23	550	500	450	5	1,135	19
280M2	457	368	419	190	65	140	18	69.0	280	40	24	105	550	130	165	520	720	23	550	500	450	5	1,135	19
280M4-6	457	368	419	190	75	140	20	79.5	280	40	24	105	550	130	165	520	720	23	550	500	450	5	1,135	19
315S2	508	406	457	216	65	140	18	69.0	315	48	28	120	610	160	160	565	805	23	660	600	550	6	1,235	24
315S4-6	508	406	457	216	80	170	22	85.0	315	48	28	120	610	160	160	565	805	23	660	600	550	6	1,265	24
315M2A:B	508	406	457	216	65	140	18	69.0	315	48	28	120	610	160	160	565	805	23	660	600	550	6	1,235	24
315M4A:B:6A	508	406	457	216	80	170	22	85.0	315	48	28	120	610	160	160	565	805	23	660	600	550	6	1,265	24
315M6B	508	40	457	216	80	170	22	85.0	315	48	28	135	610	135	205	600	805	23	660	600	550	6	1,355	24
315M2C	508	406	457	216	70	140	20	74.5	315	48	28	135	610	135	205	600	805	23	660	600	550	6	1,290	24
315M4C	508	406	457	216	80	170	22	85.0	315	48	28	135	610	135	205	600	805	23	660	600	550	6	1,320	24
315M6C	508	406	457	216	80	170	22	85.0	315	48	28	135	610	135	205	600	805	23	660	600	550	6	1,320	24
315M6D	508	406	457	216	90	170	25	95.0	315	48	28	135	610	135	205	600	805	23	660	600	550	6	1,320	24
355ML(2)	610	560	630	254	80	170	22	85.0	355	50	28	150	720	250	300	890	935	24	800	740	680	6	1,580	22
355ML (4.6)	610	560	630	254	100	210	28	106.0	355	50	28	150	720	250	300	890	935	24	800	740	680	6	1,924	22
355 H (2)	610	900		254	70	140	20	74.5	355	45	28	160	730	265	265	1045	995	24	800	740	680	6	1,854	22
355 H (4.6)	610	900		254	100	210	28	106.0	355	45	28	160	730	265	265	1045	995	24	800	740	680	6	1,924	22