



## CRISTALLO

926015



Soft PVC hose in single layer, for ducting liquids.

### DETAILS

|  |  |
|--|--|
|  SMOOTH SURFACE        | * * * * *                                  |
|  FLEXIBILITY           | * * * * *                                  |
|  ABRASION RESISTANCE   | * * *                                      |
|  TEMPERATURE RANGE   | -5 °C 60 °C                                |
|  CHEMICAL RESISTANCE | PVC Table                                  |
|  CRUSHING RESISTANCE | * *  |
|  FOR FOOD            | EU according to Declaration of Conformity. |
|  O-PHTHALATE FREE    | * * * * *                                  |

| Ø nominal<br>mm | Ø nominal<br>Inch | Ø i.d.<br>mm | Ø o.d.<br>mm | bending<br>radius<br>mm | total<br>thickness<br>mm | weight<br>meter<br>g/m | coil length<br>m | Availability |
|-----------------|-------------------|--------------|--------------|-------------------------|--------------------------|------------------------|------------------|--------------|
| 3               |                   | 3            | 6            | 24                      | 1.5                      | 25                     | 200              | In stock     |
| 4               |                   | 4            | 6            | 32                      | 1                        | 19                     | 200              | In stock     |
| 4               |                   | 4            | 7            | 32                      | 1.5                      | 32                     | 200              | In stock     |
| 4               |                   | 4            | 8            | 30                      | 2                        | 49                     | 200              | On demand    |
| 5               | 3/16              | 5            | 8            | 40                      | 1.5                      | 35                     | 200              | In stock     |
| 5               |                   | 5            | 8.3          | 40                      | 1.7                      | 45                     | 200              | On demand    |
| 6               | 1/4               | 6            | 9            | 48                      | 1.5                      | 44                     | 200              | In stock     |
| 7               |                   | 7            | 10           | 56                      | 1.5                      | 50                     | 100              | In stock     |
| 8               | 5/16              | 8            | 12           | 64                      | 2                        | 85                     | 100              | In stock     |
| 9               |                   | 9            | 13           | 72                      | 2                        | 85                     | 100              | On demand    |
| 10              | 3/8               | 10           | 14           | 80                      | 2                        | 90                     | 100              | In stock     |
| 12              | 1/2               | 12           | 16           | 120                     | 2                        | 110                    | 100              | On demand    |
| 12              | 1/2               | 12           | 17           | 120                     | 2.5                      | 140                    | 100              | In stock     |
| 13              |                   | 13           | 19           | 130                     | 3                        | 190                    | 100              | In stock     |
| 14              |                   | 14           | 19           | 140                     | 2.5                      | 160                    | 100              | In stock     |
| 15              |                   | 15           | 20           | 150                     | 2.5                      | 170                    | 100              | On demand    |
| 16              | 5/8               | 16           | 21.5         | 160                     | 3                        | 215                    | 100              | In stock     |
| 18              |                   | 18           | 23           | 175                     | 2.5                      | 200                    | 50               | On demand    |
| 18              |                   | 18           | 25           | 180                     | 3.5                      | 290                    | 50               | In stock     |
| 19              | 3/4               | 19           | 25           | 160                     | 3                        | 275                    | 50               | On demand    |
| 20              |                   | 20           | 25           | 195                     | 2.5                      | 220                    | 50               | On demand    |
| 20              |                   | 20           | 27           | 200                     | 3.5                      | 320                    | 50               | In stock     |
| 22              |                   | 22           | 30           | 220                     | 4                        | 380                    | 50               | In stock     |
| 25              | 1                 | 25           | 31           | 245                     | 3                        | 350                    | 50               | On demand    |
| 25              | 1                 | 25           | 34           | 250                     | 4.5                      | 530                    | 50               | In stock     |
| 30              |                   | 30           | 40           | 300                     | 5                        | 680                    | 30               | In stock     |
| 35              |                   | 35           | 45           | 350                     | 5                        | 760                    | 30               | In stock     |
| 40              |                   | 40           | 50           | 400                     | 5                        | 900                    | 30               | In stock     |
| 50              | 2                 | 50           | 60           | 500                     | 5                        | 1200                   | 30               | In stock     |

All technical specifications apply to a temperature of 23° C ± 2° C (ISO 291)

The tolerance on all specifications ±5% (Tolerance Percentage is applicable on ALL DATA across our range)