








OREGON

911010



PVC hose with PVC rigid spiral, for suction and ducting of air, fumes, chips, dust, textile filaments and ventilation. Self-extinguishing conforming to UL 94 V2

DETAILS

 SMOOTH SURFACE	****
 FLEXIBILITY	****
 ABRASION RESISTANCE	***
 TEMPERATURE RANGE	-10 °C 60 °C
 CHEMICAL RESISTANCE	PVC Table
 CRUSHING RESISTANCE	***
 FLAME RETARDANT	Plastic material according to UL 94 V2

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	vacuum 23 °C m/H ₂ O	bending radius mm	total thickness mm	wall thickness mm	Ø rigid spiral (AxB if oval) mm	spiral pitch mm	spiral direction	weight meter g/m	coil length m	Availability
18		18	23.2	5	18	2.6	0.7	2.5	6.2	right	140	50	On demand
20		20	26	5	20	3	0.9	2.9x2.7	6.7	right	170	50	In stock
25	1	25	30.6	5	25	2.8	0.7	2.7	7.2	right	185	50	In stock
30		30	35.6	5	30	2.8	0.8	2.5	7.5	right	225	50	In stock
32	1 1/4	32	38.2	5	32	3.1	0.8	3	8.3	right	255	50	In stock
35		35	41.6	5	35	3.3	0.8	3	8	right	300	50	In stock
38	1 1/2	38	44.4	5	38	3.2	0.8	3	8	right	310	50	In stock
40		40	46.6	4	40	3.3	0.9	3.1	8.7	right	330	50	In stock
45	1 3/4	45	51.6	4	45	3.3	0.9	3.2	9.5	right	370	50	In stock
50	2	50	57.4	4	50	3.7	1	3.6	10	right	440	50	In stock
60		60	68	4	60	4	1	3.9	11.3	right	560	50	In stock
63	2 1/2	63.2	71.2	4	63.5	4	1	3.9	10.8	right	600	50	In stock
70		70	78	4	70	4	1	3.9	12	right	640	50	In stock
75		75	83.8	4	75	4.4	1	4.3	13.5	right	730	50	In stock
76	3	76.2	85	4	76	4.4	1	4.3	13	right	730	50	On demand
80		80	89	4	80	4.5	1	4.3	14	right	790	30	In stock
90	3 1/2	90	99.4	4	90	4.7	1	4.5	14	right	860	30	In stock
100		100	109.4	4	100	4.7	1	4.5	14	right	980	30	In stock
102	4	101.6	111	4	101	4.7	1	4.5	14	right	980	30	On demand
110		110	120	4	110	5	1.2	4.8	15.3	right	1120	30	In stock
120		120	131	4	120	5.5	1.3	5.1	17	right	1300	30	In stock
125		125	136	4	125	5.5	1.3	5.2	17.5	right	1360	30	In stock
127	5	127	138	4	127	5.5	1.3	5.2	17.5	right	1360	30	On demand
130		130.5	141.9	4	130	5.7	1.3	5.4	17.5	right	1440	30	In stock
140		140.5	152.5	4	140	6	1.3	5.5	18.5	right	1600	30	In stock
150		150	162.2	4	150	6.1	1.3	5.6	19.3	right	1760	30	In stock
152	6	152.4	165.4	4	152	6.5	1.3	5.6	19.5	right	1760	30	On demand
160		160.5	173.1	4	160	6.3	1.3	6	20	right	1920	20	In stock
180		180.5	193.5	4	180	6.5	1.3	6.2	21	right	2280	20	In stock
200		200	213.2	4	200	6.6	1.4	6.4	22	right	2600	20	On demand
250		251	265.4	4	250	7.2	1.4	7	24	right	3600	15	In stock
300	12	304.8	320	4	300	7.6	1.5	7.2	24.5	right	4500	10	In stock
356	14	356	372.6	4	380	8.3	1.6	7.8	24.5	right	5600		On demand

All technical specifications apply to a temperature of 23° C ± 2° C (ISO 291)

The tolerance on all specifications ±5% (Tolerance Percentage is applicable on ALL DATA across our range)