









LUISIANA SUPERELASTIC

911022



PVC hose with rigid PVC spiral, for delivery and suction of liquids.

DETAILS

 SMOOTH SURFACE	* * * * *
 FLEXIBILITY	* * * * *
 ABRASION RESISTANCE	* * *
 TEMPERATURE RANGE	-25 °C 55 °C
 CHEMICAL RESISTANCE	PVC Table
 CRUSHING RESISTANCE	* * *

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	working pressure at 23 °C bar	vacuum 23 °C m/H ₂ O	bursting press. at 23 °C bar	bending radius mm	total thickness mm	Ø rigid spiral (AxB if oval) mm	spiral pitch mm	spiral direction	weight meter g/m	coil length m	Availability
19		19	24.6	6.5	7	19.5	60	2.8	2.3x3.5	7	right	250	50	On demand
20		20	26.2	6.5	7	19.5	65	3.1	2.5x4	7	right	275	50	In stock
25	1	25	31.6	6.5	7	19.5	100	3.3	3.2	7.4	right	330	50	In stock
30		30	37	5.5	7	16.5	125	3.5	3.4	7.5	right	420	50	In stock
32	1 1/4	32	39.2	5.5	7	16.5	135	3.6	3.6x3.4	7.7	right	460	50	In stock
35		35	41.8	5	7	15	145	3.4	3.3	7.7	right	500	50	In stock
38	1 1/2	38	45.4	4.5	7	13.5	155	3.7	3.6	7.6	right	550	50	In stock
40		40	47.8	4.5	7	13.5	160	3.9	3.6	7.8	right	610	50	In stock
45	1 3/4	45	52.8	4	7	12	180	3.9	3.6	8	right	670	50	In stock
50	2	50	58.2	3.5	7	10.5	200	4.1	4	8.3	right	810	50	In stock
51	2	51.3	59.5	3.5	7	10.5	225	4.1	3.9	8.5	right	810	50	On demand
55		55	63.6	3.5	7	10.5	225	4.3		9.8	right	860	50	On demand
60		60	69	3.5	7	10.5	245	4.5	4.4	8.3	right	970	50	In stock
63	2 1/2	63	71.2	3.5	7	10.5	260	4.1	3.9	8.5	right	1040	50	In stock
70		70	79	3.5	7	10.5	290	4.5	4.1	9	right	1200	50	On demand
75		75	85.4	2.5	7	7.5	315	5.2	4.9	9.1	right	1380	50	In stock
76	3	76	86	2.5	7	7.5	320	5		12	right	1380	50	In stock
80		80.2	90.8	2.5	7	7.5	325	5.3	5	10.5	right	1560	25	In stock
90	3 1/2	90	100.4	2.5	7	7.5	390	5.2	5	10.9	right	1800	25	On demand
100		100	112	2.5	7	7.5	430	6		11.3	right	2160	25	On demand
102	4	102.3	113.9	2.5	7	7.5	430	5.8	5.6	11.5	right	2200	25	In stock
110		110	122	2.5	5	7.5	480	6	5.6	11.5	right	2400	25	On demand
120		120	132.4	2.5	5	7.5	610	6.2		11.5	right	2850	25	On demand
125		125	137.6	2	5	6	660	6.3		11.6	right	3130	25	On demand
127	5	127	140.6	2	5	6	670	6.8		12.3	right	3130	25	In stock
150		150	164.4	2	5	6	730	7.2		14	right	4250	25	On demand
152	6	152.4	167.2	2	5	6	750	7.4		14.5	right	4250	25	In stock
200		200	218.2	1	5	3	810	9.1		21.5	right	6400	20	On demand
204	8	203.2	221.2	1	5	3	810	9	8.4	22	right	6400	20	On demand

All technical specifications apply to a temperature of 23° C ± 2° C (ISO 291)

The tolerance on all specifications ±5% (Tolerance Percentage is applicable on ALL DATA across our range)