



DETROIT

911042



Rubber hose with crush-resistant PA 6 spiral and textile support in polyester, for suction of car exhaust fumes both on the floor and on overhead reels.

DETAILS

 SMOOTH SURFACE * * *


 FLEXIBILITY * * *

 ABRASION RESISTANCE * *

 TEMPERATURE RANGE -40 °C 150 °C

 CHEMICAL RESISTANCE TPV Table

 CRUSHING RESISTANCE * * * * *

 CAUTION Do not coil the hose after use until it has cooled.

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	vacuum 23 °C m/H ₂ O	bending radius mm	wall thickness mm	rod diameter mm	spiral pitch mm	spiral direction	weight meter g/m	tensile breaking load kg	coil length m	Availability
50	2	52	68	5	120	0.75	3,5x6	19.5	left	520	>130	30	In stock
60		64	80	3.5	150	0.75	3,5x6	19.5	left	630	>130	30	In stock
75		77	93	1.5	180	0.75	3,5x6	19.5	left	750	>130	30	In stock
100		103	120	1	230	0.75	4x6,5	19.5	left	1000	>130	30	In stock
125		128	145	0.8	280	0.75	4x6,5	19.5	left	1250	>130	30	In stock
150		153	172	0.6	330	0.8	5x7,5	24	left	1500	>130	30	In stock
200		205	224	0.5	440	0.8	5x7,5	24	left	1950	>130	20	In stock

All technical specifications apply to a temperature of 23° C ± 2° C (ISO 291)

The tolerance on all specifications ±5% (Tolerance Percentage is applicable on ALL DATA across our range)