










SUPER ARIZONA PU

911074



PVC hose with PU lining and PVC rigid spiral for discharge and transport of abrasive materials.

DETAILS

 SMOOTH SURFACE	*****
 FLEXIBILITY	***
 ABRASION RESISTANCE	*****
 TEMPERATURE RANGE	-25 °C 55 °C
 CHEMICAL RESISTANCE	PU Table
 CRUSHING RESISTANCE	*****
 MICRORGANISMS RESISTANCE	*****

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	working pressure at 23 °C bar	vacuum 23 °C m/H ₂ O	bursting press. at 23 °C bar	bending radius mm	total thickness mm	Min depth PU mm	Ø rigid spiral (AxB if oval) mm	spiral pitch mm	spiral direction	weight meter g/m	coil length m	Availability
32	1 1/4	32	40.8	6	9	18	130	4.4	0.8	3.8	8.3	right	600	50	On demand
38	1 1/2	38	47	6	9	18	150	4.5	0.9	3.6	7.8	right	700	50	On demand
45	1 3/4	45	55	5	9	15	180	5	0.9		9.5	right	900	50	On demand
51	2	50.8	61.2	5	9	15	200	5.2	0.9	4.5	10	right	1050	50	In stock
63	2 1/2	63.5	74.5	4	9	12	250	5.5	0.9	4.5	11	right	1390	50	On demand
76	3	76.2	89.6	4	9	12	300	6.7	1.2	5	12	right	1900	30	On demand
89	3 1/2	88.9	104.1	3	9	9	360	7.1	1.2	6	13.5	right	2250	30	On demand
102	4	101.6	119	3	9	9	400	8.7	1.2	6.5	14.5	right	3100	30	In stock
127	5	127	146	2.5	9	7.5	510	9.5	1.4	7.5	17	right	4450	20	In stock
152	6	152.4	174.4	2	9	6	610	11	1.4	8.6x9.1	19	right	6000	20	On demand

All technical specifications apply to a temperature of 23° C ± 2° C (ISO 291)

The tolerance on all specifications ±5% (Tolerance Percentage is applicable on ALL DATA across our range)