









ARIZONA SUPERELASTIC

911075



PVC hose with rigid PVC spiral, for suction and delivery of liquids, irrigation systems, cleaning sewage drains and cesspits. Also available in antistatic version (UPON REQUEST: code 911103).

DETAILS

 SMOOTH SURFACE	* * * * *
 FLEXIBILITY	* * * * *
 ABRASION RESISTANCE	* * *
 TEMPERATURE RANGE	-25 °C 55 °C
 CHEMICAL RESISTANCE	PVC Table
 CRUSHING RESISTANCE	* * * * *

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	working pressure at 23 °C bar	vacuum 23 °C m/H ₂ O	bursting press. at 23 °C bar	bending radius mm	total thickness mm	Ø rigid spiral (AxB if oval) mm	spiral pitch mm	spiral direction	weight meter g/m	coil length m	Availability
25	1	25	34.8	7	9	21	100	4.8	4	7	right	500	50	In stock
32	1 1/4	32	41.4	6	9	18	130	4.7	4	8	right	580	50	In stock
38	1 1/2	38.2	47.6	6	9	18	150	4.7	4	8	right	700	50	In stock
40		40	49.4	6	9	18	160	4.7	4.2	8.5	right	740	50	On demand
45	1 3/4	45	55	5.5	9	16.5	180	5	4.8	9.5	right	900	50	In stock
50		50	61	5	9	15	200	5.5	5.7x5.2	10.5	right	1050	50	In stock
51	2	50.8	61.8	5	9	15	200	5.5	5	10.5	right	1050	50	On demand
60		60	71.2	4.5	9	13.5	240	5.6	5.3	11.3	right	1250	50	In stock
63	2 1/2	63.5	74.5	4.5	9	13.5	250	5.5	5.1	11.3	right	1390	50	In stock
70		70	82	4	9	12	280	6	5.5	12.3	right	1650	30	In stock
75		75	87.2	4	9	12	300	6.1	5.8	13	right	1700	30	In stock
76	3	76.2	88.4	4	9	12	300	6.1	5.8	12	right	1700	30	In stock
80		80	92.6	3.5	9	10.5	320	6.3	6.1	14	right	1850	30	In stock
89	3 1/2	88.9	102.5	3.5	9	10.5	360	6.7	6.2	14.5	right	2250	30	In stock
90	3 1/2	90	103.4	3.5	9	10.5	360	6.7	6.2	14	right	2250	30	In stock
100		100	114.6	3	9	9	400	7.3	6.5	14.5	right	2700	30	In stock
102	4	101.6	116.2	3	9	9	400	7.3	6.5	15	right	2700	30	In stock
110		110	125	3	9	9	440	7.5	7.1	15.5	right	3100	30	In stock
120		120	136.4	2.5	9	7.5	480	8.2	7.8	17	right	3600	20	In stock
125		125.5	142	2.5	9	7.5	500	8.3	7.8	17.5	right	3900	20	In stock
127	5	127	143.6	2.5	9	7.5	510	8.3	7.8	17.5	right	3900	20	In stock
130		130	147	2.5	9	7.5	520	8.5	8.1	18	right	4100	20	In stock
133		133	150	2.5	9	7.5	535	8.5	8	18	right	4200	20	In stock
140		140	157.4	2	9	6	560	8.7	8.3	18.5	right	4550	20	On demand
150		150	168	2	9	6	600	9	8.5	20	right	5000	20	In stock
152	6	152.4	170.4	2	9	6	610	9	8.7	20	right	5000	20	In stock
160		160	178.8	2	9	6	640	9.4	9	21.5	right	5600	20	In stock
200		200	226	1.5	9	4.5	800	13	12	22.5	right	9500		In stock
204	8	203.2	229	1.5	9	4.5	800	13	12	22	right	9500		In stock
250		250	279	1.5	9	4.5	1000	14.5	13x14	23.5	right	13500		On demand
254	10	254	283	1.5	9	4.5	1000	14.5	14x15	23.5	right	13500		In stock
304	12	304.8	335.8	1.5	9	4.5	1200	15.5	14x15	24.5	right	18000		On demand

All technical specifications apply to a temperature of 23° C ± 2° C (ISO 291)

The tolerance on all specifications ±5% (Tolerance Percentage is applicable on ALL DATA across our range)