







## SHARK HOSE

911079



Transparent PVC hose with PVC rigid shockproof spiral, for fish farming and carrying fish products.

### DETAILS

	SMOOTH SURFACE	*****
	FLEXIBILITY	***
	ABRASION RESISTANCE	****
	TEMPERATURE RANGE	-25 °C 55 °C
	CHEMICAL RESISTANCE	PVC Table
	CRUSHING RESISTANCE	*****

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	working pressure at 23 °C bar	vacuum 23 °C m/H <sub>2</sub> O	bursting press. at 23 °C bar	bending radius mm	total thickness mm	Ø rigid spiral (AxB if oval) mm	spiral pitch mm	spiral direction	weight meter g/m	coil length m	Availability
102	4	101.6	120	2.5	9.5	7.5	400	9.2	7.8	14	right	3250		On demand
127	5	127	149	2.5	9.5	7.5	510	11	8.8	17.5	right	3600		On demand
152	6	152.4	175.4	2	9.5	6	610	11.5	12x10	20.5	right	5600		On demand
203	8	203.2	230	2	9.5	6	800	13.5	13,5x11,5	22	right	9200		On demand
254	10	254	290	1.5	9.5	4.5	1000	18	18x14.5	29.5	right	14500		On demand
305	12	304.8	344.8	1.5	9.5	4.5	1500	20	18.5x16.5	29	right	19000		On demand
355	14	356	396	1.25	9	3.75	2200	20	18x17.5	30	right	22000		On demand
407	16	407	450	1	9	3	3000	21.5	20,5x19	33.5	right	28000		On demand

All technical specifications apply to a temperature of 23° C ± 2° C (ISO 291)

The tolerance on all specifications ±5% (Tolerance Percentage is applicable on ALL DATA across our range)