









VACUPRESS OIL PU

912909



Two-layer hose in thermoplastic PVC, PU, NITRILE RUBBER compound with embedded galvanised steel spiral with polyester yarn reinforcement with copper braid for an antistatic rendering, with outer cover made of antiabrasive PU, for suction and delivery of oils, blue diesel, diesel and bio diesel.

DETAILS

	SMOOTH SURFACE	*****
	FLEXIBILITY	***
	TEMPERATURE RANGE	-25 °C 55 °C
	CHEMICAL RESISTANCE	PVC OIL Table
	CRUSHING RESISTANCE	***
	ANTISTATIC	<2 Ohm/m

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	vacuum 23 °C m/H ₂ O	working press. at 23 °C r.1:3 bar	working press. at 23 °C r.1:4 bar	bursting press. at 23 °C bar	bending radius mm	total thickness mm	Ø steel wire mm	spiral pitch mm	spiral direction	weight meter g/m	coil length m	Availability
76	3	76	90.5	9	10	8	30	210	7.25	2	13.5	right	2700	30	In stock
80		80	94.5	9	10	8	30	220	7.3	2	14	right	2800	30	On demand
90	3 1/2	90	105.5	9	10	8	30	250	7.8	2	14	right	3250	30	On demand
102	4	102	117.5	9	10	8	30	300	7.8	2	14.5	right	3700	30	In stock
120		120	137	9	8	6	24	450	8.5	2.5	15	right	4750	20	On demand
127	5	127	144	9	7	5	21	480	8.5	2.5	15	right	5300	20	On demand
150		150	167.5	9	5	3	15	550	8.8	2.5	15.5	right	6300	20	On demand
152	6	152	169.5	9	5	3	15	550	8.8	2.5	15.5	right	6350	20	On demand

All technical specifications apply to a temperature of 23° C ± 2° C (ISO 291)

The tolerance on all specifications ±5% (Tolerance Percentage is applicable on ALL DATA across our range)