






VACUPRESS SUPERCHEMI 912954



Multilayer rubber hose with embedded galvanised steel spiral with polyester yarn reinforcement, polyolefin underlayer, for suction and delivery of corrosive liquids.

DETAILS

	SMOOTH SURFACE	*****
	FLEXIBILITY	**
	TEMPERATURE RANGE	-25 °C 80 °C
	CHEMICAL RESISTANCE	LLDPE Table
	CRUSHING RESISTANCE	***

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	vacuum 23 °C m/H ₂ O	working press. at 23 °C r.1:3 bar	working press. at 23 °C r.1:4 bar	working press. at 60 °C bar	bursting press. at 23 °C bar	bending radius mm	total thickness mm	Ø steel wire mm	spiral pitch mm	spiral direction	weight meter g/m	coil length m	Availability
19	3/4	19	27.5	9	25	15	14	80	100	4.5	0.8	5.5	right	340	60	In stock
25	1	25	33.5	9	25	15	14	77	120	4.3	1	7.5	right	430	60	In stock
28.5		28.5	37.5	9	20	15	14	65	130	4.5	1.2	8.5	right	550	60	On demand
32	1 1/4	32	41	9	18	14	14	56	150	4.5	1.2	9.5	right	590	60	In stock
38	1 1/2	38	48.5	9	17	13	13	53	200	5.3	1.4	10	right	800	30	In stock
51	2	51	62.5	9	14	10	13	42	250	5.8	1.6	11.5	right	1150	30	In stock
63	2 1/2	63	74.5	9	12	10	11	40	300	5.8	1.6	12	right	1450	30	In stock

All technical specifications apply to a temperature of 23° C ± 2° C (ISO 291)

The tolerance on all specifications ±5% (Tolerance Percentage is applicable on ALL DATA across our range)