








ARMORVIN HNP

913030



Soft PVC hose with embedded galvanized steel spiral for suction and delivery of food liquids. Heavy duty version.

DETAILS

 SMOOTH SURFACE	* * * * *
 FLEXIBILITY	* * * * *
 ABRASION RESISTANCE	* * *
 TEMPERATURE RANGE	-5 °C 65 °C
 CHEMICAL RESISTANCE	PVC Table
 CRUSHING RESISTANCE	* * *
 FOR FOOD	EU according to Declaration of Conformity.

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	vacuum 23 °C m/H ₂ O	working press. at 23 °C r.1:3 bar	bursting press. at 23 °C bar	bending radius mm	total thickness mm	Ø steel wire mm	spiral pitch mm	spiral direction	weight meter g/m	Segment Length m	coil length m	Availability
10	3/8	10	16	9.5	7	21	20	3	0.8	6.5	right	155		60	In stock
12		12	18	9.5	7	21	25	3	0.8	7	right	180		60	In stock
14		14	20	9.5	6	18	30	3	0.8	7.5	right	200		60	In stock
16	5/8	16	22	9.5	6	18	35	3	0.8	7.5	right	225		60	In stock
18		18	24.5	9.5	6	18	40	3.3	1	8	right	280		60	In stock
20		20	27	9.5	5	15	50	3.5	1	8	right	340		60	In stock
22	7/8	22	29	9.5	5	15	55	3.5	1	8.5	right	360		60	In stock
25	1	25	33.5	9.5	5	15	60	4.3	1.4	13.5	right	510		60	In stock
30		30	40	9.5	5	15	70	5	1.4	14.5	right	680		60	In stock
32	1 1/4	32	42	9.5	4.5	13.5	75	5	1.4	14.5	right	730		60	In stock
35		35	44.5	9.5	4.5	13.5	80	4.8	1.4	14.5	right	730		60	In stock
38	1 1/2	38	49	9.5	4.5	13.5	90	5.5	1.6	15	right	950		30	In stock
40		40	53	9.5	4	12	100	6.5	2	17	right	1220		30	In stock
45	1 3/4	45	58.5	9.5	4	12	110	6.75	2	18	right	1400		30	In stock
50	2	50	63.5	9	4	12	125	6.8	2	18	right	1600		30	In stock
60		60	74	9	3.5	10.5	140	7	2.5	20	right	2050		30	In stock
63	2 1/2	63	78	9	3.5	10.5	150	7.5	2.5	20	right	2250		30	In stock
70		70	86	9	3.5	10.5	180	8	2.5	20	right	2600		30	In stock
75		75	91	9	3	9	200	8	2.5	17	right	2850		30	In stock
80		80	96	9	3	9	220	8	2.5	17.5	right	3150		30	In stock
90	3 1/2	90	107	9	3	9	260	8.5	3	18	right	3750		30	In stock
100		100	118	9	3	9	300	9	3	18.5	right	4400		30	In stock
105		105	122	9	2	6	310	8.5	2.5	19.5	right	3900		20	On demand
110		110	128	9	3	9	320	9	3	19	right	4650		20	On demand
120		120	138	9	2	6	340	9	3	19.5	right	5200		20	On demand
125		125	144	9	2	6	350	9.5	3	19.5	right	5400		20	In stock
150		150	170	9	2	6	450	9.5	3	18	right	7200		20	In stock
203	8	202	224	9	2	6	900	11	3	19.5	right	9000	10		On demand

All technical specifications apply to a temperature of 23° C ± 2° C (ISO 291)

The tolerance on all specifications ±5% (Tolerance Percentage is applicable on ALL DATA across our range)