








VACUPRESS OIL

913047



Two-layer hose in thermoplastic PVC, PU, NITRILE RUBBER compound with embedded galvanised steel spiral with polyester yarn reinforcement for suction and delivery of oils, blue diesel, diesel and bio diesel.

DETAILS

| | | |
|--|---------------------|---------------|
|  | SMOOTH SURFACE | * * * * * |
|  | FLEXIBILITY | * * * * * |
|  | TEMPERATURE RANGE | -25 °C 55 °C |
|  | CHEMICAL RESISTANCE | PVC OIL Table |
|  | CRUSHING RESISTANCE | * * * |

| Ø nominal mm | Ø nominal inch | Ø i.d. mm | Ø o.d. mm | vacuum 23 °C m/H ₂ O | working press. at 23 °C r.1:3 bar | working press. at 23 °C r.1:4 bar | bursting press. at 23 °C bar | bending radius mm | total thickness mm | Ø steel wire mm | spiral pitch mm | spiral direction | weight meter g/m | coil length m | Availability |
|--------------|----------------|-----------|-----------|---------------------------------|-----------------------------------|-----------------------------------|------------------------------|-------------------|--------------------|-----------------|-----------------|------------------|------------------|---------------|--------------|
| 19 | 3/4 | 19 | 28 | 9 | 16 | 12 | 48 | 70 | 4.5 | 1 | 8.5 | right | 450 | 60 | In stock |
| 25 | 1 | 25 | 35.5 | 9 | 16 | 12 | 48 | 80 | 5.3 | 1.2 | 9 | right | 670 | 60 | In stock |
| 30 | | 30 | 40.5 | 9 | 16 | 12 | 48 | 90 | 5.3 | 1.2 | 9 | right | 770 | 60 | On demand |
| 32 | 1 1/4 | 32 | 42.5 | 9 | 16 | 12 | 48 | 100 | 5.3 | 1.2 | 9 | right | 800 | 60 | In stock |
| 35 | | 35 | 47 | 9 | 14 | 10 | 42 | 120 | 6 | 1.4 | 9 | right | 1050 | 60 | On demand |
| 38 | 1 1/2 | 38 | 51 | 9 | 14 | 10 | 42 | 125 | 6.5 | 1.4 | 9 | right | 1200 | 40 | In stock |
| 40 | | 40 | 53.5 | 9 | 14 | 10 | 42 | 130 | 6.8 | 1.4 | 9 | right | 1200 | 40 | In stock |
| 45 | 1 3/4 | 45 | 58 | 9 | 12 | 10 | 36 | 140 | 6.5 | 1.4 | 9 | right | 1340 | 40 | On demand |
| 50 | 2 | 50 | 64 | 9 | 12 | 10 | 36 | 150 | 7 | 1.6 | 9 | right | 1730 | 40 | In stock |
| 60 | | 60 | 74 | 9 | 12 | 10 | 36 | 180 | 7 | 1.6 | 9 | right | 1950 | 40 | In stock |
| 63 | 2 1/2 | 63 | 77 | 9 | 12 | 10 | 36 | 190 | 7 | 1.6 | 9 | right | 2030 | 40 | In stock |

All technical specifications apply to a temperature of 23° C ± 2° C (ISO 291)

The tolerance on all specifications ±5% (Tolerance Percentage is applicable on ALL DATA across our range)