










## SUPER RAGNO N ACQUA

915165



Food approved PVC hose with polyester yarn reinforcement and intermediate PU adhesive layer for transfer of liquids with animal fat and oils resistant cover.

### DETAILS

	SMOOTH SURFACE	* * * * *
	FLEXIBILITY	* * * * *
	ABRASION RESISTANCE	* * *
	TEMPERATURE RANGE	-5 °C 60 °C
	CHEMICAL RESISTANCE	PVC Table
	CRUSHING RESISTANCE	* * *
	FOR FOOD	EU according to Declaration of Conformity.

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	working pressure at 23 °C bar	working press. at 40 °C bar	working press. at 60 °C bar	bursting press. at 23 °C bar	bending radius mm	total thickness mm	weight meter g/m	# wires for angle n° x a°	Crush Resistance N	coil length m	Availability
12		12	20	80	66	49	240	55	4	250	doppia 24+32	600		On demand
13	1/2	13	23	80	64	48	240	45	5	340	doppia 32+32	600	100	In stock
16	5/8	16	24	60	55	40	180	100	4.25	350	doppia 36+36	600		On demand
19	3/4	19	28	60	45	30	180	100	4.5	450	doppia 24+24	600	40/60	On demand

All technical specifications apply to a temperature of 23° C ± 2° C (ISO 291)

The tolerance on all specifications ±5% (Tolerance Percentage is applicable on ALL DATA across our range)