










## RAGNO PU

915203



Antiabrasive POLYURETHANE (PU) and thermoplastic rubber compound hose with polyester yarn reinforcement for pneumatic tools in general, airbrushes and paint guns.

### DETAILS

	SMOOTH SURFACE	* * * * *
	FLEXIBILITY	* * * * *
	ABRASION RESISTANCE	* * *
	TEMPERATURE RANGE	-15 °C 60 °C
	CHEMICAL RESISTANCE	PU Table
	CRUSHING RESISTANCE	* * *
	FOR FOOD	EU according to Declaration of Conformity.

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	working pressure at 23 °C bar	working press. at 40 °C bar	working press. at 60 °C bar	bursting press. at 23 °C bar	bending radius mm	total thickness mm	weight meter g/m	# wires for angle n° x a°	coil length m	Availability
6	1/4	6	10	20	17	15	60	20	2	65	24x52°	100	On demand
8	5/16	8	12	20	17	15	60	22	2	85	18x52°	60	On demand
10	3/8	10	15	20	17	15	60	38	2.5	130	24x52°	50	On demand
13	1/2	13	19	20	17	15	60	65	3	195	24x54°	30	On demand
16	5/8	16	22.5	20	17	15	60	60	3.2	250	24x54°	25	On demand

All technical specifications apply to a temperature of 23° C ± 2° C (ISO 291)

The tolerance on all specifications ±5% (Tolerance Percentage is applicable on ALL DATA across our range)