

# HF 200


Hot water hose, two-layer, blue

**HANSA FLEX**

Last updated: 31/08/2023

## Properties

Inner tube	synthetic rubber, durable against cold and hot water with standard cleaning agents
Reinforcement	two high-tensile steel wire braids
Cover	synthetic rubber
Temp. min.	-10 °C
Elongation	+ 2 % to - 4 %
Application	high pressure cleaning equipment
Media	Cold and hot water with regular cleaning agents
Standard	EN 853 2SN
Temp. max.	150 °C
Colour	blue
Customs tariff number	40092100



## Note

The change in length of the hose is determined at max. working pressure during testing according to EN ISO 1402

## Items

Identification	DN*	Size	Inch	Inside Ø max. (mm)	Inside Ø min. (mm)	Outside Ø max. (mm)	Working pressure (bar)	Burst pressure (bar)	Bend radius min. (mm)
HF 206	6	4	1/4"	7	6.4	15.7	400	1600	100
HF 208	8	5	5/16"	8.5	7.9	17.3	400	1470	115
HF 210	10	6	3/8"	10.1	9.5	19.7	400	1320	130
HF 213	12	8	1/2"	13.5	12.7	23	400	1100	180

DN = nominal diameter, nominal width

## Frames

PHD 200	Swage ferrule for braided hose, skive ferrule, steel
---------	--