


TE 200 B

Textile hose, EN854 2TE

Properties

Application	low pressure hose for general applications
Media	mineral oil glycol water (0 °C to +70 °C) water-oil-emulsions
Inner tube	Oil resistant, synthetic rubber
Reinforcement	one or two textile braids
Cover	Oil resistant and weatherproof synthetic rubber
Colour	black
Temp. min.	-40 °C
Temp. max.	100 °C
Standard	EN 854 2TE
Customs tariff number	40093100



Items

Identification	DN*	Size	Inch	Inside Ø min. (mm)	Inside Ø max. (mm)	Outside Ø min. (mm)	Outside Ø max. (mm)	Working pressure (bar)	Test pressure (bar)	Burst pressure (bar)	Bend radius min. (mm)
TE 204 B	5	3	3/16"	4.9	5.2	10	11.6	80	160	320	35
TE 206 B	6	4	1/4"	6.4	6.9	12.6	14.2	75	150	300	40
TE 208 B	8	5	5/16"	7.9	8.4	14.1	15.7	68	136	272	50
TE 210 B	10	6	3/8"	9.5	10	15.7	17.3	63	126	252	60
TE 213 B	12	8	1/2"	12.7	13.3	18.7	20.7	58	116	232	70
TE 216 B	16	10	5/8"	15.8	16.5	22.9	24.9	50	100	200	90
TE 220 B	19	12	3/4"	18.8	19.8	26	28	45	90	180	110
TE 225 B	25	16	1"	25.4	26.2	32.9	35.9	40	80	160	150

DN = nominal diameter, nominal width

Frames

PHT	Swage ferrule for TE200, TE300, steel
PHT 200	Swage ferrule for TE200, steel