










TERMORESISTENTE KLL 125

913068



Hose made of polyester textile coated with PVC with galvanized steel spiral embedded between two layers of textile, for air-conditioning, suction of fumes and hot air.

DETAILS

	SMOOTH SURFACE	**
	FLEXIBILITY	*****
	ABRASION RESISTANCE	**
	TEMPERATURE RANGE	-5 °C 80 °C
	CHEMICAL RESISTANCE	PVC Table
	CRUSHING RESISTANCE	***
	FLAME RETARDANT	Italian Ministerial Decree 26.06.1984 with test methods UNI 8457 - 8757/A1 - 9174 - 9174/A1.

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	working pressure at 23 °C bar	vacuum 23 °C m/H ₂ O	bending radius mm	total thickness mm	wall thickness mm	Ø steel wire mm	spiral pitch mm	spiral direction	weight meter g/m	coil length m	Availability
40		41	44	0.55	1	20		0.22	0.8	20	left	85	12	In stock
51	2	51	54	0.5	0.95	25		0.22	0.8	20	left	105	12	In stock
63	2 1/2	63	66	0.45	0.9	31		0.22	0.8	20	left	130	12	In stock
70		70	73	0.43	0.85	35		0.22	0.8	20	left	145	12	In stock
76	3	76	79	0.4	0.8	36		0.22	0.8	20	left	155	12	In stock
82		82	85	0.38	0.75	41		0.22	0.8	20	left	170	12	In stock
89	3 1/2	89	92	0.3	0.7	44		0.22	0.8	20	left	180	12	In stock
102	4	102	105	0.25	0.65	51		0.22	1	25	left	215	12	In stock
108		108	111	0.23	0.6	54		0.22	1	25	left	230	12	On demand
114		114	117	0.21	0.55	57		0.22	1	25	left	240	12	In stock
121		121	124	0.20	0.5	60		0.22	1	25	left	255	12	In stock
127	5	127	130	0.18	0.45	63		0.22	1	25	left	265	12	In stock
133		133	136	0.16	0.4	66		0.22	1	25	left	280	12	In stock
140		140	143	0.15	0.38	70		0.22	1	25	left	295	12	In stock
152	6	152	156	0.14	0.35	76		0.22	1.4	32	left	380	12	In stock
160		161	165	0.12	0.32	80		0.22	1.4	32	left	410	12	On demand
165		165	169	0.12	0.3	82		0.22	1.4	32	left	420	12	In stock
178		178	182	0.1	0.25	89		0.22	1.4	32	left	450	12	In stock
203	8	203	207	0.08	0.2	101		0.22	1.4	32	left	510	12	In stock
228	9	228	232	0.06	0.15	114		0.22	1.4	32	left	570	12	In stock
254	10	254	258	0.05	0.12	127		0.22	1.6	40	left	640	12	In stock
279		279	283	0.04	0.1	139		0.22	1.6	40	left	700	12	In stock
304	12	304	308	0.03	0.05	152		0.22	1.6	40	left	770	12	In stock
330		330	334	0.02	0.03	165		0.22	1.6	40	left	830	12	In stock
355	14	355	359	0.02	0.02	177		0.22	1.6	40	left	890	12	In stock
406	16	406	410	0.02	0.01	203		0.22	1.6	40	left	1030	12	In stock
457	18	457	462	0.01	0.0005	228		0.22	1.8	40	left	1300	12	In stock
508	20	508	513	0.01	0.0004	254		0.22	1.8	40	left	1450	12	In stock
558	22	558	563	0.01	0.0003	279		0.22	1.8	40	left	1580	12	In stock
610	25	610	615	0.01	0.0002	305		0.22	1.8	40	left	1730	12	In stock

All technical specifications apply to a temperature of 23° C ± 2° C (ISO 291)

The tolerance on all specifications ±5% (Tolerance Percentage is applicable on ALL DATA across our range)