

Properties

Application	personal protection against oil jet injuries
Approval	MSHA
Colour	black
Material	polyamide (PA) or polyethylene terephthalate (PET).
Temp. max.	100 °C
Temp. min.	-40 °C
Customs tariff number	58063210



The product image may differ

Note

Extremely abrasion resistant, flame retardant.

Description

Tightly braided PA or PET threads with a maximum tensile strength, atomise the hazardous oil jet that occurs when a hose bursts.

Items

Identification	Inside Ø (mm)	Order unit	Roll length (m)	Only as roll
TGF ISO 17	17	Reel	50	
TGF ISO 20	20	Reel	50	Yes
TGF ISO 23	23	Reel	50	
TGF ISO 25	25	Reel	50	
TGF ISO 27	27	Reel	50	
TGF ISO 31	31	Reel	50	Yes
TGF ISO 33	33	Reel	50	
TGF ISO 36	36	Reel	50	Yes
TGF ISO 40	40	Reel	50	
TGF ISO 44	44	Reel	50	Yes
TGF ISO 47	47	Reel	50	
TGF ISO 53	53	Reel	50	Yes
TGF ISO 55	55	Reel	50	Yes
TGF ISO 60	60	Reel	50	
TGF ISO 66	66	Reel	50	
TGF ISO 73	73	Reel	50	Yes
TGF ISO 93	93	Reel	50	Yes
TGF ISO 112	112	Reel	50	Yes
TGF ISO 127	127	Reel	50	