

WSK NW 13 MODY


Claw coupling NW13 MODY

HANSA FLEX

Last updated: 21/03/2025

Properties

Claw distance	40 mm
Connection 1	hose connection
Connection 2	Claw coupling
Construction type	with adjusting ring
Material	hot pressed brass MS 58
Media	water
Sealing form 1	NBR form sealing ring
Temp. max.	95 °C
Temp. min.	0 °C
Customs tariff number	74122000



The product image may differ

Product details

For hose-ID (mm)	13	Inch	1/2"
Working pressure	PN 10		

Further information

The indicated working pressure refers to the coupling only and is dependent on the selected connection types.

Replacements

WSK DISA MODY	Form sealing ring for water claw coupling
---------------	---

WSK NW 19 MODY

Claw coupling NW19 MODY

HANSA FLEX

Last updated: 21/03/2025

Properties

Claw distance	40 mm
Connection 1	hose connection
Connection 2	Claw coupling
Construction type	with adjusting ring
Material	hot pressed brass MS 58
Media	water
Sealing form 1	NBR form sealing ring
Temp. max.	95 °C
Temp. min.	0 °C
Customs tariff number	74122000



The product image may differ

Product details

For hose-ID (mm)	19	Inch	3/4"
Working pressure	PN 10		

Further information

The indicated working pressure refers to the coupling only and is dependent on the selected connection types.

Replacements

WSK DISA MODY	Form sealing ring for water claw coupling
---------------	---

WSK NW 25 MODY

Claw coupling NW25 MODY

HANSA FLEX

Last updated: 21/03/2025

Properties

Claw distance	40 mm
Connection 1	hose connection
Connection 2	Claw coupling
Construction type	with adjusting ring
Material	hot pressed brass MS 58
Media	water
Sealing form 1	NBR form sealing ring
Temp. max.	95 °C
Temp. min.	0 °C
Customs tariff number	74122000



The product image may differ

Product details

For hose-ID (mm)	25
Working pressure	PN 10

Inch	1"
------	----

Further information

The indicated working pressure refers to the coupling only and is dependent on the selected connection types.

Replacements

WSK DISA MODY	Form sealing ring for water claw coupling
---------------	---