



GAMMA SILENZIOSI SILENT LINE

LA GAMMA SILENZIOSI SHAMAL include:

- **SILTEK**: la nuova linea a pistoni molto silenziosa progettata e sviluppata per le applicazioni hobbistiche e per gli artigiani, adatta per tutte le applicazioni che richiedono basse emissioni acustiche.
- **PROSIL**: compressori silenziati realizzati per risolvere il problema del rumore negli ambienti di lavoro. La riduzione della rumorosità è stata ottenuta racchiudendo la macchina dentro una cabina insonorizzata con speciali pannelli fonoassorbenti. I modelli fino a 200 litri di capacità del serbatoio sono dotati di ruote e quindi caratterizzati da una configurazione unica, che permette di combinare silenziosità e trasportabilità.
- **SILENT**: elettrocompressori che si distinguono per il progetto innovativo e la linea moderna. Sono realizzati per quelle applicazioni in cui l'attenzione per il livello di rumore assume la stessa importanza di quella per le prestazioni. In relazione ai modelli la rumorosità va da 60 a 68 dB(A).

THE SHAMAL SILENCED COMPRESSOR includes:

- **SILTEK**: the new extremely ultra-quiet piston line designed and developed for DIY and for craftsmen. Perfect for all applications requiring low noise emissions.
- **PROSIL**: silent compressor created to solve the noise problem in the work place. Noise reduction has been achieved by enclosing the machine in a sound-proof box with special sound-proof panels. Models up to 200 litres of tank capacity also feature a unique configuration which combines its silent feature with their transportable feature.
- **SILENT**: electrocompressors stand out for their innovative design and modern line. They have been created for those applications where the sound level is as important as the performance. Noise level in these models ranges from 60 to 68 dB(A).





SILTEK 50 PRO



SILTEK 50 PRO D



SILTEK 100 PRO T



Prestazioni | Performance

Nome Name	Codice Code	Gruppo Pump	Serbatoio Tank L	Potenza Power HP / kW	Cilindri Cylinder n.	Press. max. Max. press. bar / PSI	Lubrificazione Lubric.	N° Giri RPM	Aria aspirata Air displac. l/min. / CFM	Tensione freq. Voltage freq. Volt / Hz	Peso Weight kg / lbs	Dimensioni Dimensions LxPxA / WxDxH	dB(A)	Cod. a barre EAN code
SILTEK 50 PRO	B2DC2G4SHA197	OL130	50	1,3/1	2	8/116	NO	1450	150/5,3	230/50	31,5/69,5	720x320x650	59	8028403015652
SILTEK 50 PRO D	B2DC4G4SHA194	OL130	50	2,6/2	4	8/116	NO	1450	270/9,5	230/50	41,1/90,3	820x330x610	61	8028403015614
SILTEK 100 PRO T	B2FC504SHA198	OL130	100	3/2,2	6	8/116	NO	1450	315/11,1	230/50	65/143,3	1030x390x820	63	8028403015669